

RAPID R OVERLAY BLACK MINERAL

Rapid R Overlay Black Mineral is a uniquely formulated, dual-compound APP polymer modified torch-on membrane for use in renovation projects. When torched the special compound on the underside of the membrane melts and flows to form an exceptional bond with the existing mineral surfaced membrane. This single layer, durable over-roof solution is quick to apply and requires minimal preparation of the substrate, and in most situations no primer is required.



Use

For use as a torch applied, single layer overlay system in renovation projects.

Application

The bituminous membrane will be applied with a propane gas torch to the substrate. It is necessary to heat the entire surface, making sure that the compound forms a liquid mass in front of the roll to ensure that it saturates any superficial porosity. Once torched, the side laps and head laps must be pressure rolled with a long handled 15 kg roller from which a bead of compound should flow, therefore avoiding having to trowel the overlaps.

Lap sizes: 100mm side, 150mm end.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

<i>Thickness</i>	5mm
<i>Width</i>	1m
<i>Length</i>	8m
<i>Weight</i>	5kg/m ²
<i>Weight per roll</i>	40kg

Performance data

<i>Tensile Strength - longitudinal</i>	>600N/50mm
<i>Tensile Strength - transversal</i>	>500N/50mm
<i>Elongation at break - longitudinal</i>	35%
<i>Elongation at break - transversal</i>	35%
<i>Softening point</i>	140°C
<i>Cold bending</i>	-10°C

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.



IIGO Srl
Strada di Pietrara 54 A
05100 Terni (TR) Italy

info@iigo.it
www.iigo.it

