

Rapid THERMO-ADHESIVE UNDERLAY

Rapid Thermo-Adhesive Underlay is a polyester reinforced, modified bitumen underlay with a removable polyethylene film on the underside and a thermofusible polyethylene film on the upper surface.



Use

For use as a base layer in built-up roofing systems, in both new build and refurbishment projects.

Application

All surfaces to receive membrane must be clean and dry. Ensure that the membrane is accurately located, including laps, before removing the release film, and that it does not move as the film is removed. Roll out the membrane into place. The membrane is then fully bonded by thermo adhesion, via heat transfer from the torch application of the specified cap sheet.

Lap sizes: 100mm side, 150mm end.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	2.5mm
Width	1m
Length	10m
Weight	2.7kg/m ²
Weight per roll	27kg

Performance Data

Tensile Strength - longitudinal	>400N/50mm
Tensile Strength - transverse	>300N/50mm
Elongation at break - longitudinal	35%
Elongation at break - transverse	35%
Softening point	100°C
Cold bend	-15°C

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.

IIGO Srl
Strada di Pietrara 54 A
05100 Terni (TR) Italy

info@iigo.it
www.iigo.it

